

PERFORMANCE

■ Performance Report for Chemicals and Stains

Tick(V) indicates appropriate removal method of the chemical residue.

CLASSIFICATION	%	GRITTY CLEANER OR WATER	SCOTCH BRITE OR SANDPAPER
Acetic Acid	5	V	
Acetic Acid	10	V	
Acetic Acid	90		V
Acetic Acid	98		V
Acetone		V	
Aqua Regia			V
Ammonia	10	V	
Ammonium Hydroxide	5	V	
Ammonium Hydroxide	28	V	
Benzene		V	
Calcium Thiocyanate	78	V	
Chloric Hydroxide	20		V
Chloroform	100		V
Citric Acid	10	V	
Dimethyl Formamide		V	
Ethanol	95	V	
Ethyl Ether		V	
Formic Acid	88		V
Formaldehyde		V	
Furfural			V
Gasoline		V	
Hydrochloric Acid	10	V	
Hydrochloric Acid	20	V	
Hydrochloric Acid	37	V	
Isopropyl Alcohol		V	
Kerosene	20	V	
Methyl Alcohol	5	V	
Methyl Ethyl Ketone		V	
Mineral Oil		V	
Nitric Acid	10		V
Nitric Acid	30		V
Nitric Acid	40		V
Nitric Acid	70		V
Phenol	40		V
Phenol	85		V
Phosphoric Acid	25		V
Phosphoric Acid	85		V
Silver Nitrate	10	V	
Sodium Hydroxide	10	V	
Sodium Hydroxide	25	V	
Sodium Hydroxide	40	V	
Sodium Hypochlorite	5	V	
Sodium Sulphate		V	
Sulphuric Acid	25	V	
Sulphuric Acid	30	V	
Sulphuric Acid	77		V
Sulphuric Acid	96		V
Toluene			V
Xylene		V	
Zinc Chloride		V	

● Test Method - 16 hours of exposure per substance.

* For exposure to chemicals other than above, it is recommended to test on a sample piece of HANEX® to confirm the suitability for the application.

x Common domestic residues, such as the examples listed below, may be removed with water or domestic gritty cleaners.

Alcohol	Cooking Oil	Hair Dyes	Mustard	Shoe Polish	Tomato Sauce
Ballpoint Pen Ink	Crayon	Juices	Nail Polish	Soy Sauce	Vinegar
Cigarette	Curry Powder	Lipstick	Pencil Lead	Sugar	Whisky
Coffee	Eye Brow Pencil	Lotions	Salt	Tea	Wine

■ Cautions

● Products Storage

- 1) Store in a cool and shaded area, away from direct sunlight and heat. (Block off light for long-term storage)
- 2) Store on even flat floor as products can be bent stored on uneven surface for a long time.
- 3) In case of storing two or more sheets, stack them up evenly.
- 4) Do not inflict excessive pressure during storage.
- 5) Remove the protective film from the surface after products have been moved and working preparations are completed.

● Application

- 1) As our products are designed for indoor application, it is not recommend to use it in outdoor. The products may undergo change in colour and may be easily damaged when used in outdoor.
- 2) The application as flooring is not recommend as of the possibility of scratch.

● Proprietary adhesives

- 1) As the ingredient of our proprietary adhesives are same as those of products, seamless joining is possible.
- 2) Our proprietary adhesive come in a set, consists of two parts.
- 3) Our proprietary adhesive are the chemical-bonding type and should be used within six months from purchase, if possible.